

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Brake & Clutch Fluids

Version: CC28/001

Valvoline™ Brake & Clutch Fluid DOT 4

A high performance non-mineral brake fluid. Based on glycol ethers and specifically developed for hydraulic brake systems.

The high boiling point of Brake & Clutch Fluid DOT 4 guarantees safe driving and means additionally that it is safe for all materials within the brake system. It is recommended that brake and clutch fluids are refreshed every two years.

Performance levels

SAE J.1704
FMVSS 116 DOT 4
ISO 4925 Class 4

Applications

Brake & Clutch Fluid DOT 4 is suitable for all disc- and drum- braking systems, used in passenger cars, trucks and other vehicles, requiring DOT 4 level of performance.

Can be mixed with other brake fluids which are based on glycol ether or borate ester and have similar specifications. The product should not be mixed with silicone type or silicate type brake fluids.

Brake fluid should be drained from the vehicle every two years or 40.000 kilometers (24.000 miles) and refilled. Check your owner's manual for details.

Use only in its concentrated form out of a previously unopened or well sealed container. Always close the container directly after use, as the fluid absorbs moisture from the atmosphere, which reduces the service life of the product considerably. Never use drained brake fluid. Brake fluid can affect the vehicle paintwork, so remove spills immediately without rubbing.

Features and Benefits

Excellent performance

Brake & Clutch Fluid DOT 4 provides excellent performance under severe conditions, such as sport style and mountain driving.

Water absorption

Brake Fluids are hygroscopic which means that condensation water is absorbed which slowly lowers the boiling point influencing the brake performance. It is therefore recommended that the product is refreshed every 2 years.

Excellent viscosity-temperature properties

Excellent viscosity-temperature properties over a very high and low temperature range. Stable viscosity over a long period.

Brake & Clutch Fluid DOT 4 has a high (265°C.) dry boiling point.

The product can be mixed with other DOT 3 or 4 products

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used brake and clutch fluids to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Brake & Clutch Fluid DOT 4	
Colour	Clear yellow
Appearance	Clear liquid
Viscosity, mm ² /s @ -40 °C.	1400
Viscosity, mm ² /s @ 100 °C.	2.1
Specific Gravity @ 20°C. ASTM D-4052	1.04
Dry boiling point °C.	265
Wet boiling point °C.	163
Flash Point, PMCC, °C. ASTM D-92	>90
pH (50% vol.)	8.0

**This information only applies to products manufactured in the following location(s):
Europe**

People Who Know Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – CC1/002

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2013, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.